

# McKissick® Utility Crane Blocks

## 380 Series Hook Blocks

- Wide range of product available.
  - Capacity: 4,5 to 270 t - Larger Models Available.
  - Sheave Sizes: 254 - 762 mm.
  - Wire Line Sizes: 11 - 35 mm.
- Manufactured by an ISO 9001 and API Q1 certified facility.
- All single point shank hooks are genuine Crosby®, forged alloy steel, Quenched and Tempered, and have the patented **QUIC-CHECK®** markings (Duplex hooks are available on all sizes).
- All 380 Blocks are furnished standard with Roller Bearings.
- Reeving Guide Standard - All Models.
- Blocks thru 25 tons use 319N style hooks with S-4320 latches.
- Sheaves lubrication through center pin - separate lube channel to each bearing.
- Sheave fully protected by side plates.
- Dual action hook (swings and rotates).
- Repair parts available through world wide distribution network.
- Design Factor of 4 to 1 (unless otherwise noted).
- All 380 blocks, 406 mm and larger, are furnished with McKissick® Roll-Forged™ sheaves with flame hardened grooves.
- "Look for the Orange Hook . . . the mark of genuine McKissick® quality".



**SEE APPLICATION AND WARNING INFORMATION**

Para Español: [www.thecrosbygroup.com](http://www.thecrosbygroup.com) On Pages 342 - 349



The patented McKissick® Split-Nut is the standard retention system for standard crane blocks up to 80 tons.

## OPTIONS AVAILABLE

- Bronze Bushed Sheaves
- Duplex Hooks
- Swivel Tee and Shackle Assemblies
- Sheave Shrouds
- Anti Rotation - Locking Device (75 tons & larger)
- Plate Steel Cheek Weights
- Third party testing with Certification available upon request.

## Dead End Chart (Double, Triple, & Quad Sheave Blocks)

Wire Rope Size (mm)	Dimensions (mm)		Recommended Wedge Socket	
	T Thickness	U Hole Diameter	McKissick® US-422 /US-422T Utility Socket	
			Stock No.	Size
11	25.4	32.5	1044309+	US4 11
13	25.4	32.5	1044318+	US4 13
14	25.4	32.5	1044336+	US5 14
16	25.4	32.5	1044345+	US5 16
19	31.8	42.2	1044363+	US6 19
22	31.8	42.2	1038580	US7 22
25	31.8	42.2	1044417+	US8 25
28	44.5	65.0	1044426+	US10 28
32	44.5	65.0	1044435+	US10 32

\* To find Dead End Dimensions for Single Sheave blocks, refer to table on pages 267.  
+ US-422T Terminator Style.