

McKissick® Overhaul Balls

UB500 SERIES TOP SWIVELING OVERHAUL BALLS



S320 or S320N
Eye Hook



S1316A
SHUR-LOC®
Eye Hook



Both styles available with
optional McKissick® Wedge
Socket Assembly or S-421
TERMINATOR™
Wedge Socket



UWO 422T
TERMINATOR™
Wedge Only

- Sizes 4 tons through 10 tons available with Crosby's S316A "Positive Locking" SHUR-LOC® hook which may be used for lifting personnel. Meets OSHA Rule 1926.550 (g).
- Design Factor 4:1.
- The top swivel design on the UB500 assures the ball remains stationary if the wire line spins.
- The swivel incorporates a sealed roller thrust bearing together with a grease fitting for easy lubrication.
- Each ball can be equipped with the new McKissick® US-422T Wedge Socket which can be easily adjusted to fit

- various sizes of wire rope by changing the wedge (Ensure that correct wedge is used for selected wire rope size).
- All hooks used on UB500 Overhaul Balls (S320, S320N & S1316A) are forged from alloy steel. The S320 and S320N hooks come complete with latches.
- The S320 hook (PL latch) and the S320N hook (S4320 latch), with the proper latch attached, may be used for personnel lifting when secured with proper device (Bolt, nut and pin for the PL latch; Cotter pin for the S4320 latch). Meets OSHA Rule 1926.550 (g).

Overhaul Ball Assembly					Optional US-422T Wedge Sockets					
McKissick® UB500 Model No.	UB500 "E" Eye Hook Stock No.	UB500 "S" SHUR-LOC® Stock No.	Working Load Limit (t)	Weight Each (kg)	Wire Rope Size (mm)	Model No.	Wedge Socket Assy. Stock No.	Weight Each (kg)	Wedge Only Stock No.	Weight Each (kg)
MB4T35	1036000*	1036005	3.6	26.3	10	US4T	1044300	2.1	1047310	.27
MB4T85	1036009*	1036018	3.6	46.3	11	US4T	1044309	2.1	1047301	.27
MB4T150	1036027*	1036032	3.6	73.5	13	US4T	1044318	2.1	1047329	.27
MB4T200	1036036*	1036041	3.6	91.2	13	US5T	1044327	3.9	1047338	.45
MB7T85	1036045*	1036050	6.3	49.4	14	US5T	1044336	3.9	1047347	.45
MB7T150	1036054*	1036063	6.3	77.1	16	US5T	1044345	3.9	1047356	.45
MB7T200	1036072*	1036077	6.3	95.3	16	US6T	1044354	4.3	1047365	.64
MB7T285	1036081*	1036086	6.3	146	19	US6T	1044363	4.3	1047374	.64
MB10T150	1036090*	1036095	9.0	98						
MB10T200	1036099*	1036108	9.0	118						
MB10T285	1036117*	1036122	9.0	166						
MB10T350	1036126*	1036131	9.0	183	16	US6T	1044354	4.3	1047365	1.0
MB10T650	1036135*	1036140	9.0	326	19	US6T	1044363	4.3	1047374	1.1
MB12T150	1036144*	—	10.8	98	22	US8T	1044404	9.4	1047425	2.4
MB12T200	1036153*	—	10.8	117	25	US8T	1044417	9.4	1047431	2.7
MB12T285	1036171*	—	10.8	166	28	US10T	1044426	21.1	1047440	4.4
MB12T350	1036180*	—	10.8	183	32	US10T	1044435	21.1	1047459	4.5
MB12T650	1036189*	—	10.8	326						
MB15T200	1036198*	—	13.5	135						
MB15T350	1036207*	—	13.5	207						
MB15T650	1036216*	—	13.5	342						
MB15T1150	1036225*	—	13.5	595						
MB20T200	1036234*	—	18.0	135	16	US8AT	1044372	7.9	1047383	1.4
MB20T350	1036243*	—	18.0	207	19	US8AT	1044381	7.9	1047392	1.5
MB20T650	1036252*	—	18.0	342	22	US8T	1044404	9.4	1047425	2.4
MB20T1150	1036261*	—	18.0	595	25	US8T	1044417	9.4	1047431	2.7
MB25T350	1036270	—	22.5	242	28	US10T	1044426	21.1	1047440	4.4
MB25T650	1036279	—	22.5	392	32	US10T	1044435	21.1	1047459	4.5
MB25T1150	1036288	—	22.5	645						
MB30T650	1036297	—	27.0	392						
MB30T1150	1036306	—	27.0	645						

*Hook is New S-320 N Style. Replacement latch kit is S-4320. PL latch and S-4055 latch will not fit. Standard Crosby S-5 Thrust style swivels can not be used with UB500 Overhaul Balls. For replacement swivels, contact Crosby customer service.