

Lebus® Snatch Blocks



Fatigue Rated



SEE APPLICATION AND WARNING INFORMATION

Para Español: www.thecrosbygroup.com

On Pages 342-349

L-160 Series Heavy Duty Snatch Blocks

- Hook is Forged Alloy Steel — Quenched and Tempered.
- Designed for fast, efficient line changes.
- All parts are forged.
- Beaded side plate prevents rope from jamming.
- Available with hook, shackle or tailboard (pin only).
- Can be furnished with hook latch.
- Blocks furnished with dual rated wireline sheaves.
- Fatigue Rated.



L-5-H



L-5-S



L-5-T

| Block No. | Bearing Code | L-160 Stock No. | Fitting | Sheave Diam. (mm) | Working Load Limit (t)* | Wire Rope Size (mm) | Weight Each (kg.) | Rep. Sheave Stock No. | Rep. Latch Stock No. |
|-----------|--------------|-----------------|-----------|-------------------|-------------------------|---------------------|-------------------|-----------------------|----------------------|
| L-5-H | BB | 599506 | Hook | 127 | 6 | 10-13 | 6.94 | 592095 | 1096468 |
| L-5-H | RB | 599515 | Hook | 127 | 6 | 10-13 | 6.94 | 592157 | 1096468 |
| L-5-S | BB | 599524 | Shackle | 127 | 6 | 10-13 | 6.80 | 592095 | - |
| L-5-S | RB | 599533 | Shackle | 127 | 6 | 10-13 | 6.80 | 592157 | - |
| L-5-T | BB | 599542 | Tailboard | 127 | 6 | 10-13 | 4.54 | 592095 | - |
| L-5-T | RB | 599551 | Tailboard | 127 | 6 | 10-13 | 4.54 | 592157 | - |
| L-6-H | BB | 599560 | Hook | 149 | 12 | 16-19 | 14.4 | 592175 | 1096609 |
| L-6-H | RB | 599579 | Hook | 149 | 12 | 16-19 | 14.4 | 592255 | 1096609 |
| L-6-S | BB | 599588 | Shackle | 149 | 12 | 16-19 | 13.6 | 592175 | - |
| L-6-S | RB | 599597 | Shackle | 149 | 12 | 16-19 | 13.6 | 592255 | - |
| L-6-T | BB | 599604 | Tailboard | 149 | 12 | 16-19 | 8.07 | 592175 | - |
| L-6-T | RB | 599613 | Tailboard | 149 | 12 | 16-19 | 8.07 | 592255 | - |

* Ultimate Load is 4 times the Working Load Limit.

NOTE: When ordering, please specify: size, block number, hook or shackle, bronze bushed or roller bearing and wire rope size.