

# McKissick® Snatch Blocks

**Fatigue Rated®**

**SEE APPLICATION AND WARNING INFORMATION**  
 Para Español: [www.thecrosbygroup.com](http://www.thecrosbygroup.com) On Pages 342-349

## 416, 417 & 402 ALLOY SNATCH BLOCKS



**416  
WITH HOOK**



**417  
WITH SHACKLE**



**402  
TAIL BOARD**

### All Alloy Snatch Blocks

- Entire block made from heat treated alloy steel. Use of heat treated alloy gives block only 60% of the weight of blocks of comparable capacities.
- Available with a bronze bushed or roller bearing sheaves.
- Easy opening feature of "Champion" blocks retained.
- Hook and shackle assemblies can be interchanged.
- Pressure lube fittings.
- Can be furnished with hook latch.
- Blocks furnished with dual rated wireline sheaves.
- Fatigue Rated.
- All sizes are **RFID EQUIPPED**.



| Sheave Diameter (mm) | Bearing Code | Stock No.           |                        |                      | Wire Rope Size (mm) † | Working Load Limit (t)* | Weight Each (kg.)   |                        |                      | Rep. Sheave Stock No. | Rep. Latch Stock No. |
|----------------------|--------------|---------------------|------------------------|----------------------|-----------------------|-------------------------|---------------------|------------------------|----------------------|-----------------------|----------------------|
|                      |              | 416 Alloy with Hook | 417 Alloy with Shackle | 402 Alloy Tail Board |                       |                         | 416 Alloy with Hook | 417 Alloy with Shackle | 402 Alloy Tail Board |                       |                      |
| 152                  | BB           | 193427              | 168972                 | 179238               | 19-22                 | 12                      | 11.8                | 12.20                  | 6.80                 | 460824                | 1096609              |
| 152                  | RB           | 193472              | 193757                 | 179283               | 19-22                 | 12                      | 11.8                | 12.20                  | 6.80                 | 472679                | 1096609              |
| 203                  | BB           | 193490              | 168990                 | 179318               | 19-22                 | 12                      | 15.0                | 15.40                  | 9.50                 | 461173                | 1096609              |
| 203                  | RB           | 193542              | 193819                 | 179363               | 19-22                 | 12                      | 15.0                | 15.40                  | 9.50                 | 473286                | 1096609              |
| 254                  | BB           | 193613              | 193882                 | 179434               | 19-22                 | 12                      | 18.6                | 19.10                  | 13.20                | 461814                | 1096609              |
| 254                  | RB           | 193677              | 193935                 | 179498               | 19-22                 | 12                      | 18.6                | 19.10                  | 13.20                | 473785                | 1096609              |

\* Ultimate Load is 4 times the Working Load Limit.  
 † May be furnished in other wire rope sizes.

NOTE: When ordering, please specify: size, block number, hook or shackle, bronze bushed or roller bearing and wire rope size.

McKissick  
Blocks