


# McKissick® Special Application Blocks

  
**SEE APPLICATION AND WARNING INFORMATION**  
 Para Español: [www.thecrosbygroup.com](http://www.thecrosbygroup.com) On Pages 342-349

## Hay Fork Pulleys with Swivel Hook or Swivel Eye

- Forged steel eyes and hooks.
- Available Painted or Zinc Plated.
- One piece pressed steel shells.
- Edges well rounded to prevent chaffing of rope.
- Can be furnished with SS-4055 hook latch.
- Furnished with roller bearings.
- Pressure lube fittings.



**HF-1**



**HF-2**

Sheave Diameter (mm)	Block No.	Hay Fork Pulleys Stock No.		Working Load Limit (t)*	Standard Rope Size (mm)	End Fitting	Weight Each (kg.)
		Painted	Zinc Plated				
114	HF-1	170022	170594	.91	32 MR	Swivel Hook	2.72
114	HF-2	170086	170629	.91	32 MR	Swivel Eye	2.72
114	HF-3	170148	170656	.91	13 WR	Swivel Hook	2.72
114	HF-4	170200	170683	.91	13 WR	Swivel Eye	2.72
203	HF-5	170264	-	1.81	13 WR	Swivel Eye	4.99
152	HF-11	170380	-	1.81	38 MR	Swivel Hook	4.99
152	HF-12	170442	-	1.81	38 MR	Swivel Eye	4.99
152	HF-13	170503	-	1.81	16 WR	Swivel Hook	4.99
152	HF-14	170567	-	1.81	16 WR	Swivel Eye	4.99

\* Ultimate Load is 4 times the Working Load Limit.

Rope Code: MR - Manila Rope, WL - Wire Line.

## Tong Blocks

- Steel sheaves with roller bearings and pressure lubrication.
- Forged steel eyes and hooks.
- Easy opening feature shown available in 8" (203mm) size only.



**171**

Sheave Diameter (mm)	Block No.	171 Stock No.	Working Load Limit (t)*	Wire Rope Size (mm)	Weight Each (kg.)	Connection
152	TB-1	171012	.45	19	4.99	Swivel Eye
203	TB-1	171058	.91	19	5.44	Swivel Eye
254	TB-1	171101	2.27	19	13.6	Swivel Eye
305	TB-1	171156	2.27	19	15.9	Swivel Eye

\* Ultimate Load is 4 times the Working Load Limit.

## Lay Down Blocks

- All steel construction, steel sheaves mounted on antifriction bearings, grooved for maximum of 19mm wire line.
- Used to lay down drill pipe.
- Hook made to fit into end of drill pipe, handy dead end becket for returning block — hooks have handle for disengagement.



**443**

Sheave Diameter (mm)	Block No.	443 Stock No.	Working Load Limit (t)*	Wire Rope Size (mm)	Weight Each (kg.)	Type Block
114	443	171414	.23	13	5.44	Regular
152	443	171432	.45	19	7.71	Regular

\* Ultimate Load is 4 times the Working Load Limit.