


McKissick® Oilfield Servicing Blocks

Fatigue Rated™

 **SEE APPLICATION AND WARNING INFORMATION**
 Para Español: www.thecrosbygroup.com On Pages 342-349

70 SERIES BLOCKS McKissick® Oilfield Tubing Blocks utilizing new Split Nut Retention System.

Also available with Rod Hook Clevis



Revolutionary new retention system eliminates conventional threaded nut and potential problems associated with thread corrosion.

- Exclusive E-Z opening guards, no bolts to pull out and lose. Feature gives fastest possible exposure of sheave cluster for quick reeving.
- Extremely short overall length, extra weight, excellent balance for fast non-wobbling falls.
- Extra large sealed sheave bearing diameters for fully rated capacities.
- Roller thrust bearing in hook.
- Duplex hook for easy elevator operation, locks in eight positions.
- Convenient rod hook clevis available.
- Completely streamlined, no projections.
- McKissick Roll-Forged, flame hardened sheaves, grooved for proper wire line size. Contact Crosby for additional wire line sizes.
- Threaded hook parts precision machined and individually fitted for maximum performance.
- All blocks available with additional cheek weights.
- All sizes are **RFID EQUIPPED**.



The 70 Series has a spring loaded hook that is better for heavy usage and larger depths. Tends to last longer since the shock loads are somewhat absorbed.

70 Series Tubing Blocks					
Stock No.	Block Config.*	Rod Hook Clevis Working Load Limit (lbs.)	Working Load Limit (t)	Wire Line Size (mm)	Weight Each (kg.)
111792	20" 73	25,000	67.5	22	803
111890	20" 73-A	25,000	67.5	22	823
111818	24" 73	35,000	90	25	1195
111916	24" 73-A	35,000	90	25	1247
111827	30" 73	45,000	135	28	2018
111925	30" 73-A	45,000	135	28	1845
128793	30" 74	45,000	135	28	1996
125545	30" 74-A	45,000	135	28	2024

* Spring loaded duplex hook assuring ample travel for efficient tubing operations. No load carrying threads.

80 SERIES BLOCKS

Also available with Rod Hook Clevis



The 80 Series has no spring loaded hook and is better for shallow depths and rework.

80 Series Tubing Blocks					
Stock No.	Block Config.	Rod Hook Clevis Working Load Limit (lbs.)	Working Load Limit (t)*	Wire Line Size (mm)	Weight Each (kg)
112130	17" 83	15,000	45	22	491
112238	17" 83-A	15,000	45	22	503
112149	20" 82	15,000	45	22	510
112247	20" 82-A	15,000	45	22	564
112158	20" 83	25,000	67.5	22	727
112256	20" 83-A	25,000	67.5	22	753
112167	24" 82	25,000	67.5	25	816
112265	24" 82-A	25,000	67.5	25	830
112176	24" 83	35,000	90	25	998
112274	24" 83-A	35,000	90	25	991
117475	24" 84	35,000	90	25	1225
117484	24" 84-A	35,000	90	25	1247
112185	30" 83	45,000	135	28	1225
112283	30" 83-A	45,000	135	28	1617
117493	30" 84	45,000	135	28	1746
117509	30" 84-A	45,000	135	28	1873

*