

# McKissick® Oilfield Servicing Blocks

**Fatigue Rated**

**SEE APPLICATION AND WARNING INFORMATION**  
 Para Español: [www.thecrosbygroup.com](http://www.thecrosbygroup.com) On Pages 342-349

## ALL ALLOY



**434  
WITH  
HOOK**



**435  
WITH SHACKLE**



**401  
TAIL BOARD**

### High Capacity Snatch Blocks

- Entire block made from heat treated alloy steel. Use of heat treated alloy gives block only 60% of the weight of blocks of comparable capacities.
- Available with bronze bushed sheaves.
- Easy opening feature of "Champion" blocks retained.
- Pressure lube fittings.
- Can be furnished with hook latch.
- Fatigue Rated.
- All sizes are **RFID EQUIPPED**.



Sheave Diameter (mm)	Bearing Code	Stock No.			Wire Rope Size (mm)*	Working Load Limit (t)†	Weight Each (kg.)		
		434 with Hook	435 with Shackle	401 Tail Board			434 with Hook	435 with Shackle	401 Tail Board
203	BB	208894	168295	179149	25	25	41	46	23
203	BB	302522	302568	302602	28	25	41	46	23
254	BB	208901	208956	179158	25	25	49	54	29
254	BB	208910	208965	179167	32	25	49	54	29
254	BB	302531	302577	302611	28	25	49	54	29
305	BB	208929	208974	179176	25	30	75	83	43
305	BB	302540	302586	302620	28	30	75	83	43
356	BB	208938	208983	179185	25	30	82	90	50
356	BB	302559	302595	302639	28	30	82	90	50
305	BB	-	8027291	8027292	28	60	-	143	73

\* May be furnished in other wire rope sizes.

† Ultimate Load is 4 times the Working Load Limit.

NOTE: When ordering, please specify: size, block number, hook or shackle, and wire rope size.