

# Western Regular Wire Rope Blocks



**SEE APPLICATION AND WARNING INFORMATION**

Para Español: [www.thecrosbygroup.com](http://www.thecrosbygroup.com)

On Pages 342-349

## Diamond & Oval Pattern Regular Wire Rope Blocks



T-641-B

- Laser cut painted side plates (can be furnished galvanized upon request).
- Grade 5 bolts secured with lock washers and staked nuts.
- All sizes feature bronze bushed steel sheaves with larger bearing diameter for extended block life.
- New style hanger for fitting attachment
- Available with hanger only (no fitting).
- For reeving information, see page 346.

Block Size (in.)	Fitting	Diamond Pattern with Bronze Bushed Steel Sheaves		Oval Pattern with Bronze Bushed Steel Sheaves	
		641-B Single	642-B Double	661-B Single	662-B Double
4	T	781586	782193	791183	791593
6	T	781611	782219	791218	791619
8	T	781639	782237	791236	791637
10	T	781657	782255	791254	791655
4	S	785886	786199	795884	796197
6	S	785902	786206	795900	796204
8	S	785920	786224	795928	796222
10	S	785948	786242	795946	796240
6	J	782102	782503	791502	791904
8	J	782120	782521	791520	791922
10	J	782148	782549	791548	791940
6	E	782004	782406	791307	791708
8	E	782022	782424	791325	791726
10	E	782040	782442	791343	791744



S-642-B

Block Size (in.)	Sheave Size (mm)		Wire Rope Size (mm)	Working Load Limit (t)*		Weight Each (kg)	
	Outside Diam.	Rim Thickness		641 661 Single	642 662 Double	641 661 Single	642 662 Double
4	102	19.1	10	.91	1.82	3.6	5.0
6	152	25.4	10	2.72	3.63	6.8	9.5
8	203	31.8	16	3.63	5.44	12.7	18.6
10	254	31.8	16	3.63	6.35	17.2	27.2

\* Ultimate Load is 4 times the Working Load Limit.

Fitting Type: T = Hook with Latch; S = Shackle; J = Oblong Eye; E = Swivel Shackle Eye