


McKissick® Trawl & Try Net Blocks


SEE APPLICATION AND WARNING INFORMATION
 Para Español: www.thecrosbygroup.com On Pages 342-349

J-452
Oblong Swivel Eye



Double Rig Trawl Blocks

- Steel sheave with flame hardened groove, for maximum wear under abrasive conditions.
- Double row, permanently sealed tapered roller bearings.
- Pressure lubrication throughout.
- All steel construction.
- Hot Dip galvanized.

| Sheave Dia. and Block No. | 452 Stock No. | Working Load Limit (t)* | Weight Each (kg) | Sheave Dimensions (mm) | |
|---------------------------|---------------|-------------------------|------------------|------------------------|---------------|
| | | | | Outside Diameter | Rim Thickness |
| 8" J-452 | 130655 | 9.07 | 21.8 | 203 | 95.5 |
| 12" J-452 | 130673 | 9.07 | 38.6 | 305 | 95.5 |
| 16" F-452 | 130682 | 18.14 | 53.0 | 406 | 95.5 |
| 18" J-452 | 2015467 | 22.50 | 136 | 457 | 138 |
| 22" F-452 | 130708 | 27.22 | 109 | 559 | 95.5 |

* Ultimate Load is 4 times the Working Load Limit.

NOTE: 18" J-452 utilizes a Manganese Steel Sheave that is not flame hardened.



F-453 6"

Try Net Blocks

- Forged steel swivel eyes.
- Hot Dip galvanized.
- 6" 453 - Pressed steel side plates with flared edges. Figure 8 grooved, self-lubricating bronze bushed sheaves, with pressure lube fittings. 453 has an extra wide throat opening to allow fittings to pass through.
- 6" 454 - Forged side plates designed to eliminate rope jamming. Wide throat opening and pressure lube fitting on sheave and eye fitting.
- 8" 454 - Forged steel side plates designed to eliminate possibility of rope jamming. Furnished with sealed tapered bearings. Flame hardened forged steel sheaves for wear resistance.

| Sheave Dia. and Block No. | Bearing Type | Try Net Block Stock No. | Working Load Limit (t)* | Weight Each (kg) | Sheave Dimensions (mm) | |
|---------------------------|-----------------|-------------------------|-------------------------|------------------|------------------------|---------------|
| | | | | | Outside Diameter | Rim Thickness |
| 6" F-453 | Bronze Bushed | 769886 | 4.54 | 15.9 | 152 | 70.0 |
| 6" F-454 | Needle Bearing | 2001763 | 4.54 | 10.4 | 152 | 70.0 |
| 8" J-454 | Tapered Bearing | 130726 | 9.07 | 16.3 | 203 | 73.0 |

* Ultimate Load is 4 times the Working Load Limit.



F-454 6"



J-454 8"